

EloStar Master



Highlights

- Up to 100 users per lock
- Up to 3 authentication options can be configured variable for each user
- RFID (EM/HITAG, MIFARE Classic)
- Standard or flexible one-time codes can be selected as option
- 2-lock operation possible

Standard functions	EloStar Master 300 - 325
Motor lock / spring bolt lock	3xx series
Motor lock / pull-push 50 N	4xx series
Multiple lock operation	2
Security class (VdS/ECBS)	2/B
Classic FlatControl keypad	■
Individual user matrix	■
Manager code/system code	■
Master code	■
User code	99
Physical code carrier: chip card	100
Service code	■
CIT service code	■
Quick unlocking code	■
Dual code (opening/configuration)	■
Parallel code (only for 2 locks)	■
Protocol/date and time	3000
PC software TwinComm USB (optional)	■
Time programs	■
Partial blocking	■
Unlocking/opening delay	■
Blocking time	■
Manipulation blockout	■
Automatic locking	■
External battery (emergency power supply)	■
Power supply unit connection	■
Optional EloXTII hold-up connection (VdS C)	■
Duress alarm*	■
Lock status*	■
External release/blocking*	■

Standard functions	EloStar Master 300 - 325
Door contact connection	■
Alarm if door is open too long	■
Configuration/audit	chip card
Network connection (with TwinIP)	■
Lock management software for a network (TwinNet GO!)	■
Server network software TwinNet	■
MultiPad GO!	■

Additional functions (incl.)	RFID card	Standard OTCs	Flexible OTCs
EloStar Master 300/400		■	
EloStar Master 305/405			■
EloStar Master 310/410	EM40XX/HITAG	■	
EloStar Master 315*/415*	EM40XX/HITAG		■
EloStar Master 320/420	MIFARE classic	■	
EloStar Master 325/425	MIFARE classic		■

* EM/HITAG one-time codes only with PIN code

* only in connection with EloXT II

