



## Low Weight SAFES ROBUR LW Grade 0



### **Burglary protection**

The safes are tested in accordance with the European standard EN-1143-1 and certified by ECB·S.

### **Description**

The safes have a low weight thanks to a special insulation material.

Wall thickness: 25mm

Door thickness: 84mm

4-way locking bolt system including a continuous dog-bar on the hinge side.

### **Locking**

As standard the safe is provided with:

One key-lock Class A with two keys.

Available as option:

Extra keylock

Mechanical combination lock

Electronic combination lock

### **Anchoring**

Conduit for anchoring.

### **Alarm**

One conduit at the rear side.

Option

Cable through the hinge for alarm connection.

### **Finish**

Off white, RAL 9010.

### **Weight and measurement**

See overleaf

### **Fittings**

See overleaf

# Dimensions in mms and kilos

Safe Robur LW Grade 0							
Model	40	50	80	500	900	1200	1500
<b>External measurements mm</b>							
Height	475	550	850	550	950	1250	1540
Width	450	450	450	550	550	550	550
Depth *	445	445	445	515	515	515	515
<b>Internal measurements mm</b>							
Height	425	500	800	500	900	1200	1490
Width	400	400	400	500	500	500	500
Depth	330	330	330	400	400	400	400
<b>Clear opening of the door mm</b>							
Height	363	438	738	438	838	1138	1428
Width	354	354	354	454	454	454	454
<b>Weight kilos</b>	65	71	100	87	134	166	200
<b>Volume litre</b>	56	66	105	100	180	240	298
<b>Standard fittings</b>	1 shelf	1 shelf	2 shelves	1 shelf	2 shelves	2 shelves	3 shelves

\* External depth  
+ 55 mm for handle

## INTERIOR FITTINGS



Lockable cupboard, small



Lockable cupboard, large

Interior fittings	External height mm
A. Shelf	-
B. Lockable cupboard, small	155
C. Lockable cupboard, large	355

We reserve the right to alter the specification without prior notice.



**Head office**  
**Robur Safe AB**  
Lundbyvägen 8  
SE-311 68 SLÖINGE  
Phone: +46 346 260 260

info@robursafe.com

www.robursafe.com