



Low Weight SAFES ROBUR LW Grade I



Burglary protection

The safes are tested in accordance with the European standard EN-1143-1 and certified by ECB·S.

Description

The safes have a low weight thanks to a special insulation material.

Wall thickness: 25mm

Door thickness: 84mm

4-way locking bolt system including a continuous dog-bar on the hinge side.

Locking

As standard the safe is provided with:

One key-lock Class A with two keys.

Available as option:

Extra keylock

Mechanical combination lock

Electronic combination lock

Anchoring

Conduit for anchoring.

Alarm

One conduit at the rear side.

Option

Cable through the hinge for alarm connection.

Finish

Off white, RAL 9010.

Weight and measurement

See overleaf

Fittings

See overleaf

Dimensions in mms and kilos

Safe Robur LW Grade I							
Model	40	50	80	500	900	1200	1500
External measurements mm							
Height	475	550	850	550	950	1250	1540
Width	450	450	450	550	550	550	550
Depth *	445	445	445	515	515	515	515
Internal measurements mm							
Height	425	500	800	500	900	1200	1490
Width	400	400	400	500	500	500	500
Depth	330	330	330	400	400	400	400
Clear opening of the door mm							
Height	363	438	738	438	838	1138	1428
Width	354	354	354	454	454	454	454
Weight kilos	67	74	104	91	137	170	204
Volume litre	56	66	105	100	180	240	298
Standard fittings	1 shelf	1 shelf	2 shelves	1 shelf	2 shelves	2 shelves	3 shelves

* External depth
+ 55 mm for handle

INTERIOR FITTINGS



Lockable cupboard, small



Lockable cupboard, large

Interior fittings	External height mm
A. Shelf	-
B. Lockable cupboard, small	155
C. Lockable cupboard, large	355

We reserve the right to alter the specification without prior notice.



Head office
Robur Safe AB
Lundbyvägen 8
SE-311 68 SLÖINGE
Phone: +46 346 260 260

info@robursafe.com

www.robursafe.com