



# ROBUR

4

## Low Weight SAFES ROBUR LW Grade II



### **Burglary protection**

The safes are tested in accordance with the European standard EN-1143-1 and certified by ECB·S.

### **Description**

The safes have a low weight thanks to a special insulation material.

Wall thickness: 50mm

Door thickness: 106mm

4-way locking bolt system including a continuous dog-bar on the hinge side.

### **Locking**

As standard the safe is provided with:

One key-lock Class A with two keys.

Available as option:

Extra keylock

Mechanical combination lock

Electronic combination lock

### **Anchoring**

Conduit for anchoring.

### **Alarm**

One conduit at the rear side.

Option

Cable through the hinge for alarm connection.

### **Finish**

Off white, RAL 9010.

### **Weight and measurement**

See overleaf

### **Fittings**


See overleaf

# Dimensions in mms and kilos


Safe Robur LW Grade II							
Model	40	50	80	500	900	1200	1500
<b>External measurements mm</b>							
Height	525	600	900	600	1000	1300	1590
Width	500	500	500	600	600	600	600
Depth *	495	495	495	565	565	565	565
<b>Internal measurements mm</b>							
Height	425	500	800	500	900	1200	1490
Width	400	400	400	500	500	500	500
Depth	330	330	330	400	400	400	400
<b>Clear opening of the door mm</b>							
Height	393	468	768	468	868	1168	1458
Width	384	384	384	384	484	484	484
<b>Weight kilos</b>	140	155	210	190	275	340	405
<b>Volume litre</b>	56	66	105	100	180	240	298
<b>Standard fittings</b>	1 shelf	1 shelf	2 shelves	1 shelf	2 shelves	2 shelves	3 shelves

\* External depth  
+ 55 mm for handle

## INTERIOR FITTINGS




Lockable drawer



Lockable cupboard




Combination lock  
S&G 8550 MP



Extra shelf



Electronic pincode lock



Sliding frame



Security cupboard

Interior fittings	External height mm
A. Shelf	-
B. Lockable cupboard, small	155
C. Lockable cupboard, large	355
D. Sliding frame for A4/folio	-
E. Security cupboard	420
F. Lockable drawer, small	155
G. Lockable drawer, large	355

We reserve the right to alter the specification without prior notice.



**Head office**  
**Robur Safe AB**  
Lundbyvägen 8  
SE-311 68 SLÖINGE  
Phone: +46 346 260 260

info@robursafe.com

www.robursafe.com