



Low Weight SAFES

ROBUR LW Grade III



Burglary protection

The safes are tested in accordance with the European standard EN-1143-1 and certified by ECB·S.

Description

The safes have a low weight thanks to a special insulation material.

Wall thickness: 50mm

Door thickness: 106mm

4-way locking bolt system including a continuous dog-bar on the hinge side.

Locking

As standard the safe is provided with:

One key-lock Class B with two keys.

Available as option:

Extra keylock

Mechanical combination lock

Electronic combination lock

Anchoring

Conduit for anchoring.

Alarm

One conduit at the rear side.

Option

Cable through the hinge for alarm connection.

Finish

Off white, RAL 9010.

Weight and measurement

See overleaf


Fittings

See overleaf


Dimensions in mms and kilos

Safe Robur LW Grade III							
Model	40	50	80	500	900	1200	1500
External measurements mm							
Height	525	600	900	600	1000	1300	1590
Width	500	500	500	600	600	600	600
Depth *	495	495	495	565	565	565	565
Internal measurements mm							
Height	425	500	800	500	900	1200	1490
Width	400	400	400	500	500	500	500
Depth	330	330	330	400	400	400	400
Clear opening of the door mm							
Height	393	468	768	468	868	1168	1458
Width	384	384	384	384	484	484	484
Weight kilos	240	265	360	325	480	595	710
Volume litre	56	66	105	100	180	240	298
Standard fittings	1 shelf	1 shelf	2 shelves	1 shelf	2 shelves	2 shelves	3 shelves

* External depth
+ 55 mm for handle



Lockable drawer



Lockable cupboard




Combination lock
S&G 8550 MP



Extra shelf



Electronic pincode lock



Sliding frame



Security cupboard

INTERIOR FITTINGS

Interior fittings	External height mm
A. Shelf	-
B. Lockable cupboard, small	155
C. Lockable cupboard, large	355
D. Sliding frame for A4/folio	-
E. Security cupboard	420
F. Lockable drawer, small	155
G. Lockable drawer, large	355

We reserve the right to alter the specification without prior notice.



Head office
Robur Safe AB
Lundbyvägen 8
SE-311 68 SLÖINGE
Phone: +46 346 260 260

info@robursafe.com

www.robursafe.com