



## Deposit safes Grade II

### As per EN 1143-2

The deposit safes are ideal for businesses with large cash handling, where the staff must be able to deposit notes, envelopes and other securities safely without having access to the material themselves inside the safe.

Even with an unlocked deposit drawer, you cannot access the material in the safe.



Pearl white, RAL 9010.



Standard equipped with two changeable key locks, one on the door and one on the drawer. Electronic combination locks on special order.



Models 80, 900 and 1200 are fitted with one shelf as standard. More options such as a drawer on the side or back of the safe are available.



Prepared for anchoring. (Bolts are not included). Cabinets under 1000 kg shall be anchored.



Burglary protection certified by ECB·S according to EN 1143-2.

## WEIGHT AND MEASUREMENTS

	II 40	II 50	II 80
<b>External measurements</b> H * W * D* mm	720 * 560 * 600	820 * 560 * 600	1120 * 560 * 600
<b>Internal measurements</b> H * W * D mm	230 * 400 * 330	330 * 400 * 330	630 * 400 * 330
<b>Deposit opening</b> H * W * D mm	100 * 270 * 190	100 * 270 * 190	100 * 270 * 190
<b>Weight</b> kg	455	510	670
<b>Volume</b> liter	30	44	83
<b>Standard fitting</b>	_____	_____	1 shelf

\* External depth - The wheel (handle) increases the external depth by 55 mm.



	II 500	II 900	II 1200
<b>External measurements</b> H * W * D* mm	835 * 660 * 670	1235 * 660 * 670	1535 * 660 * 670
<b>Internal measurements</b> H * W * D mm	330 * 500 * 400	730 * 500 * 400	1030 * 500 * 400
<b>Deposit opening</b> H * W * D mm	100 * 270 * 190	100 * 270 * 190	100 * 270 * 190
<b>Weight</b> kg	660	890	1050
<b>Volume</b> liter	66	146	206
<b>Standard fitting</b>	_____	1 shelf	1 shelf

\* External depth - The wheel (handle) increases the external depth by 55 mm.

## OPTIONAL FITTINGS

- **The deposit drawer placed at the rear side of the safe**
- **Chute 125 mm through wall, incl. deposit drawer**
- **Chute and deposit drawer on the side of the safe**
- **Preparation for cable through hinge**

---

We reserve the right to alter the specification without prior notice.



**Head office:**

Robur Safe AB  
Lundbyvägen 8  
311 68, Slöinge  
Sweden

☎ 0346 260 260

✉ [info@robursafe.com](mailto:info@robursafe.com)

🌐 [www.robursafe.com](http://www.robursafe.com)