

Deposit safes Grade III As per EN 1143-2

The deposit safes are ideal for businesses with large cash handling, where the staff must be able to deposit notes, envelopes and other securities safely without having access to the material themselves inside the safe.

Even with an unlocked deposit drawer, you cannot access the material in the safe.





Pearl white, RAL 9010.



Standard equipped with two changeable key locks, one on the door and one on the drawer. Electronic combination locks on special order.



Models 80, 900 and 1200 are fitted with one shelf as standard. More options such as a drawer on the side or back of the safe are available.



Prepared for anchoring. (Bolts are not included). Cabinets under 1000 kg shall be anchored.



Burglary protection certified by ECB·S according to EN 1143-2.

WEIGHT AND MEASUREMENTS

	III 50	III 80
720 * 560 * 600	820 * 560 * 600	1120 * 560 * 600
230 * 400 * 330	330 * 400 * 330	630 * 400 * 330
100 * 270 * 190	100 * 270 * 190	100 * 270 * 190
480	540	700
30	44	83
		1 shelf
	230 * 400 * 330 100 * 270 * 190 480	230 * 400 * 330 330 * 400 * 330 100 * 270 * 190 100 * 270 * 190 480 540





	III 500	III 900	III 1200
External measurements H*W*D*mm	835 * 660 * 670	1235 * 660 * 670	1535 * 660 * 670
Internal measurements	330 * 500 * 400	730 * 500 * 400	1030 * 500 * 400
Deposit opening H * W * D mm	100 * 270 * 190	100 * 270 * 190	100 * 270 * 190
Weight kg	690	925	1100
Volume liter	66	146	206
Standard equipment		1 shelf	1 shelf

^{*} External depth - The wheel (handle) increases the external depth by 55 mm.

OPTIONAL FITTINGS

- The deposit drawer placed at the rear side of the safe
- Chute 125 mm through wall, incl. deposit drawer
- Chute and deposit drawer on the side of the safe
- Preparation for cable through hinge

We reserve the right to alter the specification without prior notice.



Head office:

Robur Safe AB Lundbyvägen 8 311 68, Slöinge Sweden



☑ info@robursafe.com

