



Deposit safes Grade IV

As per EN 1143-2

The deposit safes are ideal for businesses with large cash handling, where the staff must be able to deposit notes, envelopes and other securities safely without having access to the deposits themselves inside the safe.

Even with an unlocked deposit drawer, you cannot access the material in the safe.



Pearl white, RAL 9010.



Standard equipped with three changeable key locks, two on the door and one on the drawer. Electronic combination locks on special order.



Fitted with one shelf as standard. Prepared for cable through hinge. More options such as a drawer on the side or back of the safe are available.



Prepared for anchoring. (Bolts are not included). Cabinets under 1000 kg shall be anchored.



Burglary protection certified by ECB·S according to EN 1143-2.

WEIGHT AND MEASUREMENTS

	IV 500	IV 900	IV 1200
External measurements H * W * D* mm	880 * 690 * 730	1280 * 690 * 730	1580 * 690 * 730
Internal measurements H * W * D mm	330 * 500 * 400	730 * 500 * 400	1030 * 500 * 400
Deposit opening H * W * D mm	100 * 270 * 190	100 * 270 * 190	100 * 270 * 190
Weight kg	900	1160	1400
Volume liter	66	146	206
Standard equipment	_____	1 shelf	1 shelf

* External depth - The wheel (handle) increases the external depth by 55 mm.



IV 500



IV 900



IV 1200

OPTIONAL FITTINGS

- **The deposit drum placed at the rear side of the safe**
- **Chute 125 mm through wall, incl. deposit drum**
- **Chute and deposit drum on the side of the safe**

We reserve the right to alter the specification without prior notice.



Head office:
Robur Safe AB
Lundbyvägen 8
311 68, Slöinge
Sweden

☎ 0346 260 260

✉ info@robursafe.com

🌐 www.robursafe.com