

## Safe Grade V As per EN 1143-1 & NT Fire 017-60P

Safes on Grade IV are used for protecting cash, valuables and documents against burglary and fire. These safes are also approved for storing weapons and explosives.







Pearl white, RAL 9010.



Standard equipped with two changeable key locks. Combination lock or electronic combination lock on special order.



Standard interior is 1-3 shelves. More options are available.



Prepared for anchoring. (2  $^{*}$  M16 anchoring bolts included for modell IV 500). Cabinets under 1,000 kg shall be anchored.



The safes have as standard a hole through the hinge for optional alarm connection.



Fire protection certified by SBSC according to NT Fire 017 - 60P. For the models: 500, 900, 1200 and 1500.



Burglary protection certified by SBSC & ECB·S according to European standard EN 1143-1.



Core Diamond drill certified by ECB·S according to EN 1143-1 CD. For the models 900, 1200, 1500, 1800/2 och 1800/3 on special order.

## **WEIGHT AND MEASUREMENTS**

	V 500	V 900	V 1200	
External measurements H*W*D*mm	695 * 690 * 730	1095 * 690 * 730	1395 * 690 * 730	
Internal measurements	500 * 500 * 400	900 * 500 * 400	1200 * 500 * 400	
Weight kg	750	1120	1380	
<b>Volume</b> liter	100	180	240	
Fire protection	1 shelf	2 shelves	2 shelves	
Standard fittings	NT Fire 017 - 60P	NT Fire 017 - 60P	NT Fire 017 - 60P	
* External depth - The wheel (handle) increases the external depth by 55 mm.				



V 1500

V 1800/2

V 1800/3

	V 1500	V 1800/2	V 1800/3
External measurements  H*W*D*mm	1695 * 690 * 730	2015 * 920 * 870	2015 * 1240 * 870
Internal measurements  H * W * D mm	1500 * 500 * 400	1820 * 730 * 540	1820 * 1050 * 540
Weight kg	1630	2450	3000
<b>Volume</b> liter	300	717	1032
Fire protection	3 shelves	3 shelves	3 shelves
Standard fittings	NT Fire 017 - 60P	_	_

<sup>\*</sup> External depth - The wheel (handle) increases the external depth by 55 mm.

V 500

V 900

V 1200

## **OPTIONAL FITTINGS**



Extendable shelf



Adjustable shelf



Extendable hanging folder frame



Lockable locker 155mm - 1 door The key lock can be changed to \*Robur Pin 1600



Lockable locker 155mm - 2 doors The key lock can be changed to \*Robur Pin 1600



Lockable locker 155mm - 3 doors The key lock can be changed to \*Robur Pin 1600



Lockable locker 355mm - 1 door The key lock can be changed to \*Robur Pin 1600



Lockable locker 355mm - 2 doors The key lock can be changed to \*Robur Pin 1600



Lockable drawer



Alarm package



\*\*Electronic combination lock Insys combilock 200 simplex



Deposit cupboard



\*Robur Pin 1600



Diamond drill Protection


We reserve the right to alter the specification without prior notice.




**Head office:** Robur Safe AB Lundbyvägen 8 311 68, Slöinge Sweden



**L** + 46 346 260 260





<sup>\*\*</sup> Other lock options are possible.