



Server security cabinets RSKS

As per SSF 3492

Suitable for burglar-proof storage of servers, workstations, etc.



Light gray, RAL 9002.



Standard equipped with a changeable key lock.
Electronic combination lock on special order.



Standard equipped with a thermostatically controlled fan system and one power strip with 6 outlets. More options are possible.



The safes have as standard a hole through the hinge for optional alarm connection.



Prepared for anchoring. (Bolts are not included).
Cabinets under 150kg shall be anchored.



Burglary protection certified by SBSC according to SSF 3492.

WEIGHT AND MEASUREMENTS

	RSKS 840	RSKS 1200	RSKS 1200/2	RSKS 1600
External measurements H * W * D* mm	840 * 630 * 885	1200 * 750 * 900	1200 * 750 * 1116	1600 * 750 * 900
Internal measurements H * W * D mm	610 * 530 * 800	1005 * 635 * 815	1005 * 635 * 978	1405 * 635 * 815
Weight kg	235	270	345	325
Volume liter	320	690	860	960
Number of units (19" rack)	9U	19U	19U	28U
Number of doors	One door	One door	Two doors	One door

* External depth - The wheel (handle) increases the external depth by 55 mm.



	RSKS 1600/2	RSKS 1900	RSKS 1900/2	RSKS 2000
External measurements H * W * D* mm	1600 * 750 * 1116	1900 * 750 * 900	1900 * 750 * 1116	2000 * 870 * 1100
Internal measurements H * W * D mm	1405 * 635 * 978	1705 * 635 * 815	1705 * 635 * 978	1950 * 1150 * 85
Weight kg	415	360	470	470
Volume liter	1190	1160	1440	1440
Number of units (19" rack)	28U	34U	34U	36U
Number of doors	Two doors	One door	Two doors	One door

* External depth - The wheel (handle) increases the external depth by 55 mm.

OPTIONAL FITTINGS



Extendable, ventilated shelf



Adjustable, ventilated shelf



Power strip with 6 outlets



19" rack, four posts



19" rack, 2 posts



Fan module with four fans



We reserve the right to alter the specification without prior notice.



Head office:
Robur Safe AB
Lundbyvägen 8
311 68, Slöinge
Sweden

☎ + 46 346 260 260
✉ info@robursafe.com
🌐 www.robursafe.com