



## Safe Grade I

As per EN 1143-1 & EN 15659 - LFS 30

Suitable to protect documents and valuables from fire and theft.  
The safes are aimed at private homes and businesses with less protection needs.



Pearl white, RAL 9010.



Standard equipped with an adjustable key lock.  
Electronic combination lock on special order.



Standard interior is a shelf.



Prepared for anchoring. (1 \* M12 anchoring bolt included).  
Cabinets under 1,000 kg shall be anchored.



Fire protection certified by ECB·S according to EN 15659 level LFS 30 minutes.



Burglary protection certified by ECB·S according to European standard EN 1143-1.

## WEIGHT AND MEASUREMENTS

	I-340	I-440
<b>External measurements</b> H * W * D* mm	340 * 500 * 345	440 * 500 * 432
<b>Internal measurements</b> H * W * D mm	262 * 424 * 216	362 * 424 * 302
<b>Weight</b> kg	93	119
<b>Volume</b> liter	24	46
<b>Standard fitting</b>	1 shelf	1 shelf

\* External depth - The wheel (handle) increases the external depth by 55 mm.



I-340



I-440

## OPTIONAL FITTINGS



Electronic combination lock  
PS 610

We reserve the right to alter the specification without prior notice.



**Head office:**  
Robur Safe AB  
Lundbyvägen 8  
311 68, Slöinge  
Sweden

+ 46 346 260 260  
info@robursafe.com  
www.robursafe.com