



Safes for storage of explosives SP

Grade III

Adapted for outdoor use with sealing and drainage strips that prevent moisture inside the cabinets, lockable cover on the door that protects the lock. Equipped with 2 lifting loops on the top of the cabinet for easy transport between workplaces.

The safes are prepared with ground connections for connection of lightning protection. Detached warehouses for storing more than 500 kg of explosive goods must have protection against lightning.



Prepared for placement outdoors and are anti-rust painted and equipped with drainage strips.



Standard equipped with two changeable key locks.
Combination lock or electronic combination lock on special order.



Standard equipped with a fire extinguisher and a weather protection over the handle and lock.



Prepared for anchoring. (2 * M16 bolts included).
Safes under 1000kg shall be anchored.



Fire protection certified by SBSC according to NT Fire 017 – 60P alternatively fire tested according to EI60.



Burglary protection certified by ECB·S according to European standard SS-EN 1143-1/EN 1143-1.

WEIGHT AND MEASUREMENTS

	III 900SP	III 1500SP	III 1700SP
External measurements H * W * D mm	1290 * 660 * 728	1890 * 660 * 728	2090 * 1020 * 1628
Internal measurements H * W * D mm	900 * 500 * 400	1500 * 500 * 400	1700 * 860 * 1300
Weight kg	815	1175	2950
Volume liter	180	300	1900
Standard fittings	2 shelves	3 shelves	—
Fire protection	NT Fire 017 - 60P	NT Fire 017 - 60P	EI60

* External height - incl. plinth 100mm.



1. Reinforced, weather-protected roof.
2. Lifting eyes welded to the body.
3. Steel lid covering the lock and handle.
4. Powder extinguisher with protecting cover included.
5. connection devices for thunder protection.

We reserve the right to alter the specification without prior notice.



Head office:
Robur Safe AB
Lundbyvägen 8
311 68, Slöinge
Sweden

+ 46 346 260 260
info@robursafe.com
www.robursafe.com