

Safe deposit lockers BF4 Double width


Robur has manufactured and installed several million safe deposit lockers around the world. BF4 is manufactured in our factory in Sweden with the highest possible safety and the lockers come with a timeless design.





The lockers are manufactured in natural anodized aluminium which gives a timeless design. The cover plates, ceiling and plinths are manufactured in metal and painted in graphite grey. The body is in aluzinc-coated metal.

Available with both mechanical **BC** and electronical **EBC** locking system:





• Electronical **EBC**: double locking system where the customer operates the individual lock and the control lock is operated electronically.

Robur Safe offers an automated safe deposit system detailed in a seperate leaflet. In both systems **EBC** and **BC**, only the customer with the personal key can operate and have access to the locker.



The columns have three different heights: 1830, 2030 and 2230 mm. Standard locker heights are 300, 325, 425 and 500 mm. As standard, no inner containers are included.



The lockers can be combined as desired within the free space for lockers between ceiling and plinth. On the following pages, our standard locker combinations are described and developed according to the market's requirements.



Constructed according to standard SSF 1048-2.

Total height per column: 1830 mm including plinth H37 mm; Total height for lockers: 1725 mm; Locker width: 640 mm; Locker depth: 490 mm; Approximate weight per column: 190 kg

Figure	BF4 01-1830 DW
Locker height Qty * Height mm	4 * 325 1 * 425
Number of lockers	5

2030 Total height per column: 2030 mm including plinth H37 mm; Total height for lockers: 1925 mm; Locker width: 640 mm; Locker depth: 490 mm; Approximate weight per column: 200 kg	
Figure	BF4 01-2030 DW
Locker height Qty * Height mm	1 * 300 5 * 325
Number of lockers	6

<u>2230*</u> Total height per column: 2230 mm including plinth H37 mm; Total height for lockers: 2125 mm; Locker width: 640 mm; Locker depth: 490 mm; Approximate weight per column: 210 kg * Mechanical locking BC is not recommended for this height	
Figure	BF4 01-2230 DW
Locker height Qty * Height mm	5 * 325 1 * 500
Number of lockers	6

As standard, no inner containers are included.

We reserve the right to alter the specification without prior notice.



Head office: Robur Safe AB Lundbyvägen 8 311 68, Slöinge Sweden



L + 46 346 260 260

☐ info@robursafe.com

www.robursafe.com