

Vault and Strongroom doors are essential where a higher level of security is required for storing cash, valuables and controlled drugs.

Our range of doors are designed to suit security requirements from Grade I to Grade XI EX-CD. Each door features a frame that can be integrated into a concrete wall, adapted for a Prefabricated Strongroom, or equipped with a Grip Frame.

Additionally, Robur Safe offers emergency doors from Grade III to Grade XI EX-CD.





Primed finish.



As standard the Strongroom door Grade X EX CD is provided with two changeable key locks.

- On special order:
  - Electronic combination lock and/or one extra lock.
  - Emergency opening from inside.

As standard the Strongroom door Grade X EX CD is provided with:

- Alarm cabling between door and frame through one of the hinges.
- One door stop holder is delivered with the door.
- Two magnetic switches to indicate open door.




Burglary protection certified by SBSC according to the European standard EN 1143-1. Fire protected according to El90.

Blast tested according to the European standard EN 1143-1. Diamond drills tested according to the European standard EN 1143-1.

## **PRODUCT SPECIFICATIONS**

	RVD Grade X EX CD
Standard clear opening measure	2000 * 900
Max. clear opening dimensions for certified door	2400 * 1400
Max. clear opening dimensions for uncertified door	3200 * 2100
Frame	The frame is designed for 500 mm wall thickness.
Weight <sup>kg</sup>	2100





## HANGING OF DOOR AND GATE:






fig. 1. Door - right hung Gate - left hung








fig. 4. Door - left hung Gate - left hung

We reserve the right to alter the specification without prior notice.



## Head office: Robur Safe AB Lundbyvägen 8 311 68, Slöinge Sweden

**L** + 46 346 260 260

- ∑ info@robursafe.com
- $\bigoplus$  www.robursafe.com